

MAINTENANCE GUIDE FOR YAMAHA F150

ltem	Actions	20 Hours	100 Hours
Anode(s) (external)	Inspection or replacement as necessary		\bigcirc $lacktriangle$
Anode(s) (cylinder head, thermostat cover)	Inspection or replacement as necessary		0
Anodes (exhaust cover, cooling	Replacement		
water passage cover, Rectifier			
Regulator cover)			
Battery (electrolyte level,	Inspection		
terminal)	·		
Battery (electrolyte level,	Fill, charging or replacing as		
terminal)	necessary		
Cooling water leakage	Inspection or replacement as		
	necessary		
Cowling lock lever	Inspection		$\circ \bullet$
Engine starting condition/noise	Inspection	\circ	$\circ \bullet$
Engine idle speed/noise	Inspection	\circ	$\circ \bullet$
Engine oil	Replacement	0	\circ
Engine oil filter (cartridge)	Replacement		\circ
Fuel filter (can be	Inspection or replacement as		\circ
disassembled)	necessary		
Fuel line (High pressure)	Inspection		
Fuel line (High pressure)	Inspection or replacement as		
	necessary	U	O
Fuel line (Low pressure)	Inspection		
Fuel line (Low pressure)	Inspection or replacement as necessary	0	0
Fuel pump	Inspection or replacement as		
	necessary		
Fuel/engine oil leakage	Inspection	0	0
Gear oil	Replacement	0	0
Greasing points	Greasing	0	0
Impeller/water pump housing	Inspection or replacement as		
	necessary		
Impeller/water pump housing	Replacement	0	0
Power trim and tilt unit	Inspection	0	0
Propeller/propeller nut/cotter	Inspection or replacement as		
pin	necessary		\cup
PCV (Pressure Control Valve)	Inspection or replacement as		
	necessary		
Shift link/shift cable	Inspection, adjustment or	0	
	replacement as necessary		



MAINTENANCE GUIDE FOR YAMAHA F150

Item	Actions	20 Hours	100 Hours
Spark plug(s)	Inspection or replacement as		
	necessary		
Spark plug caps/spark plug	Inspection or replacement as		
wires	necessary	U	O
Water from the cooling water	Inspection	\cap	\circ
pilot hole		<u> </u>	<u> </u>
Throttle link/throttle	Inspection, adjustment or		
cable/throttle pick-up timing	replacement as necessary		
Thermostat	Inspection or replacement as		\cap
	necessary		
Timing belt	Inspection or replacement as		\cap
	necessary		O O
Valve clearance	Inspection and replacement		
Cooling water inlet	Inspection	0	\circ
Main switch/stop switch/choke	Inspection or replacement as		\cap
switch	necessary		O
Wire harness connections/wire	Inspection or replacement as	0	\circ
coupler connections	necessary		
(Yamaha) Meter/gauge	Inspection	0	0